

Printing date 11.02.2008 Revision: 11.02.2008

### 1 Identification of the substance/preparation and of the company/undertaking

Product details

Trade name:

2104 Osmo Opaque Gloss Wood Stain, white

Application of the substance / the

preparation Coating compound/ Surface coating/ paint

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Further information obtainable

*from:* Product safety department

Phone: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

Information in case of

*emergency:* emergency phone no. Berlin (24h): +49 (0) 30 / 19240

### 2 Hazards identification

*Hazard description:* Not applicable.

Information concerning

particular hazards for human and

environment: The product does not have to be labelled due to the calculation procedure of the

"General Classification guideline for preparations of the EU" in the latest valid version.

Classification system: The classification is according to the latest editions of the EU-lists, and extended by

company and literature data.

#### 3 Composition/information on ingredients

Chemical characterization

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy

EINECS: 265-150-3

Additional information: For the wording of the listed risk phrases refer to section 16.

### 4 First aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult

doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 2)

Xn; R 65-66 10-25%



Printing date 11.02.2008 Revision: 11.02.2008

# Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

(Contd. of page 1)

After swallowing: If swallowed, seek medical advice immediately and show this container or label.

5 Fire-fighting measures

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant

foam.

For safety reasons unsuitable

extinguishing agents:

Water with full jet

Special hazards caused by the substance, its products of

combustion or resulting gases:

Formation of toxic gases is possible during heating or in case of fire.

Protective equipment:

Mouth respiratory protective device.

Additional information Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official

regulations.

#### 6 Accidental release measures

Person-related safety precautions: Keep away from ignition sources.

Ensure adequate ventilation

Measures for environmental

protection: Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Measures for cleaning/collecting: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,

sawdust).

## 7 Handling and storage

Handling:

*Information for safe handling:* Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

Use only in well ventilated areas. Prevent formation of aerosols.

Information about fire - and

*explosion protection:* Keep ignition sources away - Do not smoke.

Storage:

Requirements to be met by

storerooms and receptacles: Store in a cool location.

Store only in the original receptacle.

Information about storage in one

common storage facility: Do not store together with alkalis (caustic solutions).

(Contd. on page 3)



Printing date 11.02.2008 Revision: 11.02.2008

## Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

(Contd. of page 2)

Do not store together with oxidizing and acidic materials.

Further information about

storage conditions: Keep container tightly sealed.

Store receptacle in a well ventilated area.

Protect from frost.

Protect from heat and direct sunlight.

### 8 Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

#### 64742-48-9 Naphtha (petroleum), hydrotreated heavy

TWA (8H) Short-term value: 1000 mg/m<sup>3</sup>

Source UK SIA

**Additional information:** The lists valid during the making were used as basis.

Personal protective equipment: General protective and hygienic

measures: Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

**Protection of hands:** Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/

the preparation.

Selection of the glove material on consideration of the penetration times, rates of

diffusion and the degradation

Material of gloves Nitrile rubber, NBR

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

For the permanent contact gloves made of the following materials

are suitable: Nitrile rubber, NBR

As protection from splashes gloves made of the following

materials are suitable: Nitrile rubber, NBR

Eye protection: Goggles recommended during refilling

**Body protection:** Protective work clothing

(Contd. on page 4)



Printing date 11.02.2008 Revision: 11.02.2008

# Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

(Contd. of page 3)

9 Physical and	d c l	hemi	ical	properties
----------------	-------	------	------	------------

**General Information** 

Form:	Fluid			
Colour:	White			
Odour:	Mild			
Change in condition				
Melting point/Melting range:	Undetermin			

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: > 180°C (DIN 51751)

*Flash point:* >57°C (DIN 52231)

*Ignition temperature:* 240°C

**Self-igniting:** Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

 Lower:
 0.6 Vol %

 Upper:
 7.0 Vol %

Vapour pressure: 3 hPa [20°C]

**Density at 20°C:** 1.25 - 1.35 g/cm³ (DIN 51757)

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

Viscosity:

*Kinematic at 20°C:* < 40 s (ISO 6 mm)

Solvent separation test: < 3 % (ADR 2.2.1.4f)

Solvent content:

VOC(EC) < 300 g/l (VOC-max. = 300 g/l (2010 A/d))

### 10 Stability and reactivity

Thermal decomposition /

conditions to be avoided: No decomposition if used and stored according to specifications.Dangerous reactions Reacts with fabric soaked in the product (e.g. cleaning wool).

Exothermic reaction.

Forms heat. Self igniting.

Reacts with acids, alkalis and oxidizing agents.

(Contd. on page 5)



Printing date 11.02.2008 Revision: 11.02.2008

## Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

(Contd. of page 4)

Dangerous decomposition

products: Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Additional information:

Warning:

Wash out any used cloth impregnated with this product immedeately after use or store

in an airtight container (danger of self-ingnition).

### 11 Toxicological information

#### Acute toxicity:

LD/LC50 values relevant for classification:					
64742-48-9 Naphtha (petroleum), hydrotreated heavy					
Oral	LD50	>2000 mg/kg (rat)			
Dermal	LD50	>2000 mg/kg (rat)			
Inhalative	LC50/4 h	>5 mg/l (rat)			
96-29-7 2-butanone oxime					
Oral	LD50	3700 mg/kg (rat)			
Dermal	LD50	200-2000 mg/kg (rat)			
Inhalative	LC50/4 h	20 mg/l (rat)			

Primary irritant effect:

on the skin: At long or repeated contact with skin it may cause dermatitis due to the degreesing

effect of the solvent.

on the eye: Irritating effect.

Sensitization: No sensitizing effects known.

Additional toxicological

*information:* The product is not subject to classification according to the calculation method of the

General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any

harmful effects to our experience and the information provided to us.

### 12 Ecological information

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for

water

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 6)



Printing date 11.02.2008 Revision: 11.02.2008

## Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

(Contd. of page 5)

### 13 Disposal considerations

**Product:** 

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

European waste catalogue

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

15 01 10 packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

Land transport ADR/RID (cross-border)

ADR/RID class: 3 Flammable liquids.

Danger code (Kemler):30UN-Number:1263Packaging group:IIIHazard label:3

Description of goods: 1263 PAINT

Maritime transport IMDG:

IMDG Class:-UN Number:1263Label3Packaging group:IIIMarine pollutant:NoProper shipping name:PAINT

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class: 3
UN/ID Number: 1263
Label 3
Packaging group: III
Proper shipping name: PAINT

(Contd. on page 7)



Printing date 11.02.2008 Revision: 11.02.2008

## Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

(Contd. of page 6)

### 15 Regulatory information

Labelling according to EU

guidelines:

The product is not subject to identification regulations under EU Directives and the

Ordinance on Hazardous Materials (German GefStoffV).

Although this product is not subject to identification regulations, we recommend that

the safety suggestions are observed.

Safety phrases: 2 Keep out of the reach of children.

24/25 Avoid contact with skin and eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

46 If swallowed, seek medical advice immediately and show this container or label.

51 Use only in well-ventilated areas.

Special labelling of certain

preparations:

Warning:

Wash out any used cloth impregnated with this product immedeately after use or store

in an airtight container (danger of self-ingnition).

Contains 2-butanone oxime. May produce an allergic reaction. Safety data sheet available for professional user on request.

National regulations:

VOC(EC) < 300 g/l (VOC-max. = 300 g/l (2010 A/d))

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

*Relevant R-phrases* 65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

**Department issuing MSDS:** product safety department

Contact: Hr. Dr. Starp

GB