



Resin Remover



Procedural instruction

It can occasionally happen that wood resin bleeds out of and is visible on the surface of colored garden products, this is a natural occurrence with wood and as such can normally not be 100 % avoided.

The resin is sticky and will crystallize over time. It is normally easier to remove once crystallized.

So as not to destroy the finished surface of the wood Osmo technicians developed and created a product which can deal with this challenge, namely the "Osmo resin remover set".

We recommend the following procedure when using this product:

- Remove larger amounts of resin using a blunt scraper until you are left with only a thin film, please take care not to damage the colored surface finish when removing the resin.
- Wet the supplied lint free cloth with resin remover and rub off the remaining film on the surface.
- The colored surface will lose some of its gloss level and may appear dull, here we recommend rubbing on a thin coat of Osmo Clear Oil Wood Finish (color code 000) with a lint free cloth and allowing it to dry.
- Please read the instructions carefully on all products!

Caution: Flammable. Keep out of the reach of children. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Contains 2-butanonoxime. May produce an allergic reaction. If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas. **Warning:** Wash out any used cloth immediately after use or store in an airtight container (danger of self-ignition).

Safety data sheet available for professional user on request.

Osmo Holz und Color GmbH & Co. KG, Affhüppen Esch 12, D-48231 Warendorf, phone +49 (0)2581/922-100, fax +49 (0)2581/922-200, www.osmo.de, info@osmo.de

02/08 GB